

Corner originally set as a post in 1820 by John Hendricks with the following witnesses: 36" beech bearing north 9 degrees, thence west 24 links; and a 36" dogwood bearing south 22 degrees, thence east 38 links.(M.C. Atlas P. 11) A survey by Wm. Case on March 23,1857 indicates a rock with no witnesses.(Lawrence Legal Book P. 21) A survey by John Coyner on December 5,1895 indicates a rock set by a former surveyor in 1857.(Lawrence Legal Book P.42) Corner referenced by Woerner on 6/19/48 and called a brass pin. Corner referenced by Monroe on 6/13/60 and called a brass pin. Corner referenced by Wilcoxen on 3/9/76 and and called a brass plug. Corner Referenced by Gries on 7/7/88 and called a brass plug. Corner referenced by Kiste on 7/23/99 and called a brass plug. Corners excavated on 5/27/04 and no points were found. A #205 cast iron Harrison Monument was set in position as the corner by GPS.

16041201		
REF.	DISTANCE	DESCRIPTION
Ï	46.58	Mag nail w/brass washer top wooden guard post
2.	50.60'	Mag nail w/brass washer top wooden guard post
3.	66.72	Mag nail w/brass washer top wooden guard post
4,	62,47	Mag nail w/brass washer top wooden guard post
5.	1.88'	S to face of curb median
6.	44.98'	Mag nail w/brass washer @ concrete and asphalt meets
	],	